

WILD Series
Thermal Imaging

Thermal Imaging Monocular Wild 650

Technical Specifications



ThermTec Technology Co., Ltd. Email: info@thermeyetec.com

Website: https://www.thermeyetec.com





WILD 650

Key Features

- 640*512 thermal resolution, NETD≤18mk;
- Automatic object detection and AI distance measurement;
- 1x--4x continuous digital zoom;
- Various pesudo colors;
- Joystick control design, wheel focusing realises one-hand operation;
- Super large aperture offers better temperature radiation capturing capability;
- 1024*768 resolution with 0.39 inch OLED display;
- Up to 8h continuous working for lithium battery;
- Forest/Target outline mode

Applications

- Night hunting
- Observation
- Rescue operations
- Hiking and traveling

Specifications

Model	Wild650
Resolution	640x512
Pixel Pitch	12μm
NETD	18mk@300k
Spectral range	8-14μm
Frame rate	50HZ
Detection Range	2,600m
	Optics
Objective lens	50mm
Field of view	8.8° x 7.0°
Magnification	2.8X
Digital Zoom	1-4X continuous zoom
Eye relief	40mm
Exit pupil	6mm
Diopter	±5D
	Display
Туре	AMOLED
Resolution	1024x768
Display size	0.39 inch
Color palette	6
Image mode	Forest/Target outline mode

Function	
Photo/video playback	Yes
Language	Multiple-languages
Built-in Memory	64GB
PIP	Yes
AI Distance Measurement	Yes
Heat Track	Yes
GPS	Yes
Real-time Notification	Yes
OSD Recording	Yes
EIS	Yes
	Battery
Internal battery	Replaceable and Rechargeable Li-ion Battery (18650x1)
Battery life	8h
	Interface
Type-C	Supports battery charging, data transfer, USB video output
Hotspot	Yes, App remote control
	Environment
Working temperature	-20°C—+50°C
Protection Level	IP67
Weight, g	510±5g
Size, mm	190.2(L)x76.3(W)x65.6(H)
	Accessories
External Cable	USB cable
Other Accessories	Palm strap/Protective bag/Non-dust cloth and etc.

Accessories







Charger (X1)

Bag(x1)



Lanyard(x1)

Lens cloth (x1)

User manual (x1)

Dimension

Unit: mm





