

Page: 1

Assembly Grease

Revision No: 1

Compilation date: 04/03/2016

## Section 1: Identification of the substance/mixture and of the company/undertaking

## 1.1. Product identifier

Product name: Stalon Assembly Grease

1.2. Relevant identified uses of the substance or mixture and uses advised against

### 1.3. Details of the supplier of the safety data sheet

Company name: Stalon AB

Stal**o**n 104 912 97 Malgomaj Sweden

Tel: +46(0)940-500 35

Email: info@stalon.nu

1.4. Emergency telephone number

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CHIP: -: R66

Most important adverse effects: Repeated exposure may cause skin dryness or cracking.

2.2. Label elementa

Label elements under CHIP:

Hazard symbols: Symbol not required.

Risk phrases: R66: Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

PBT: This substance is not identified as a PBT substance.

### Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

STAPA ALUMINIUM 4NL/92

# Stalon Assembly Grease

# Page: 2

EINECS	CAS	CHIP Classification		CLP Classification	Percent
231-072-3	64742-48-9	Xn: R65; -: R10; F: R11; -: R66; -:	-		10-30%
		R15			

# Non-hazardous ingredients:

EINECS	CAS	CHIP Classification	CLP Classification	Percent
-	64742-65 0	-	-	50-70%
INNTALC PO	WDER			
2388779	14807-96-6	-	-	1-10%
GRAPHITE (S	YNTHETIC) MIL	LED		
-	7440-44-0	-	-	1-10%
PROPYLENE	CARBONATE			
203-572-1	108-32-7	Xi: R36	-	<1%
LOWTAC 20	00			
			_	<1%

Section -	4: First ai	d measures
-----------	-------------	------------

4.1. Description of first aid	measures
Skin contac	t: Remove all contaminated clothes and footwear immediately unless stuck to skin.
	Drench the affected skin with running water for 10 minutes or longer if substance is still
	on skin. Consult a doctor.
Eye conta	t: Bathe the eye with running water for 15 minutes. Consult a doctor.
Ingestio	n: Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water
	to drink immediately. Consult a doctor.
Inhalatio	n: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a
	doctor.
4.2. Most important sympt	oms and effects, both acute and delayed
Skin conta	t: There may be irritation and redness at the site of contact.
Eye contac	t: There may be pain and redness. The eyes may water profusely.
Ingestio	n: There may be soreness and redness of the mouth and throat. There may be difficulty
	swallowing. Nausea and stomach pain may occur.
Inhalatio	n: There may be irritation of the throat with a feeling of tightness in the chest.
4.3. Indication of any imme	ediate medical attention and special treatment needed
mmediate / special treatmei	t: Not applicable.
ection 5: Fire-fighting me	asures

### Stalon Assambly Grease

Page: 3

### 5.1. Extinguishing media

**Extinguishing media:** Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

### 5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

### 5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

### Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Mark out the contaminated area

with signs and prevent access to unauthorised personnel. Turn leaking containers leak

-side up to prevent the escape of liquid.

### 6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

### 6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for

disposal by an appropriate method.

### 6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

# Section 7: Handling and storage

### 7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed.

### 7.3. Specific end use(s)

Specific end use(s): No data available.

## Section 8: Exposure controls/personal protection

8.1. Control parameters

Workplace exposure limits: Not applicable.

8.2. Exposure controls

Respiratory protection: Respiratory protection not required.

Hand protection: Impermeable gloves.

### Stalon Assambly Grease

Page: 4

# Eye protection: Safety glasses with side-shields. Ensure eye bath is to hand.

Skin protection: Impermeable protective clothing.

### Section 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

State: Paste

Colour: Black

Odour: Perceptible odour

9.2. Other information

### Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

## 10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

## 10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

## Section 11: Toxicological information

11.1. Information on toxicological effects

Skin contac	There may be irritation and redness at the site of contact.		
Eye contac	: There may be pain and redness. The eyes may water profusely.		
Ingestion	: There may be soreness and redness of the mouth and throat. There may be difficulty		
	swallowing. Nausea and stomach pain may occur.		
Inhalatio	: There may be irritation of the throat with a feeling of tightness in the chest.		

### Stalon Assambly Grease

Page: 5

12.1. Toxicity

### 12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

## 12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

### 12.5. Results of PBT and vPvB assessment

PBT identification: This substance is not identified as a PBT substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

## 13.1. Wasts treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

### Section 14: Transport information

Transport class: This product is not classified for transport.

## Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### 15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

by the supplier.

# Section 16: Other information

### Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

\* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and 3: R10: Flammable.

R11: Highly flammable.

R15: Contact with v/ater liberates extremely flammable gases.

R36: Irritating to eyes.

## Stalon Assambly Grease

Page: 6

Į.

R65: Harmful: may cause lung damage if swallowed. R66: Repeated exposure may cause skin dryness or cracking.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.