

WILD Series
Thermal Imaging

Thermal Imaging Monocular Wild 325

**Technical Specifications** 



ThermTec Technology Co., Ltd. Email: info@thermeyetec.com

Website: https://www.thermeyetec.com





# **WILD325**

#### **Key Features**

- 384\*288 thermal resolution, NETD≤18mk;
- Automatic object detection and AI distance measurement;
- 1x--4x continuous digital zoom;
- Various pesudo colors;
- Joystick control design, wheel focusing realises one-hand operation;
- Super large aperture offers better temperature radiation capturing capability;
- 1024\*768 resolution with 0.39 inch OLED display;
- Up to 10h continuous working for lithium battery;
- Forest/Target outline mode

### **Applications**


- Night hunting
- Observation
- Rescue operations
- Hiking and traveling

# Specifications

Model	Wild325
Resolution	384x288
Pixel Pitch	12μm
NETD	18mk@300k
Spectral range	8-14µm
Frame rate	50HZ
Detection Range	1,300m
	Optics
Objective lens	25mm
Field of view	10.5° x 7.9°
Magnification	2.4X
Digital Zoom	1-4X continuous zoom
Eye relief	40mm
Exit pupil	6mm
Diopter	±5D
	Display
Туре	AMOLED
Resolution	1024x768
Display size	0.39 inch
Color palette	6
Image mode	Forest/Target outline mode

	Function
Photo/video playback	Yes
Language	Multiple-languages
Built-in Memory	64GB
PIP	Yes
AI Distance Measurement	Yes
Heat Track	Yes
GPS	Yes
Real-time Notification	Yes
OSD Recording	Yes
EIS	Yes
	Battery
Internal battery	Replaceable and Rechargeable Li-ion Battery (18650x1)
Battery life	10h
	Interface
Type-C	Supports battery charging, data transfer, USB video output
Hotspot	Yes, App remote control
	Environment
Working temperature	-20°C—+50°C
Protection Level	IP67
Weight, g	470±5g
Size, mm	190.2(L)x69.3(W)x58.7(H)
	Accessories
External Cable	USB cable
Other Accessories	Palm strap/Protective bag/Non-dust cloth and etc.

## **Accessories**



## **Dimension**

Unit: mm

